



ICESTRIKER™

STAINLESS STEEL SPREADER



MADE IN FINLAND

380 liter • For pickups, UTVs etc. • Sand, salt, mix • All in stainless steel • GPS-speedcontrol • Optional pre-wet

ICESTRIKER STAINLESS STEEL

SPREADER APPLICATIONS

Our new spreader is built to meet the requirements of the UTV and European light-pickup segment. Thanks to the convenient size of the spreader, it fits most kinds of small machines, like utility vehicles, tool carriers and mini-loaders. This device is perfect for spreading at parking lots, courtyards, walkways and pedestrian paths.

SPREADER DESIGN

The high quality stainless steel hopper body guarantees a longlasting corrosion-free use. The hopper surface is easy to clean and maintain, and provides a smooth material flow. The spreader is designed for spreading bulk sand and gravel, bulk/bag salt, sand-salt mixes and fertilisers. Can optionally be equipped with pre-wet kit.



STANDARD CONTROLLER

The color screen controller lets you customize your spreading session according to your current situation. Automatic GPS-speedcontrol adjusts the amount of spreading material (g/m^2) according to your vehicle speed, while manual mode lets you insert a fixed auger speed. The controller additionally collects and saves essential data to an USB memory, allowing you to generate spreading reports. The controller also makes it easy to turn on functions, like vibrator, beacon and work light, from inside the cabin.

GPS-speedcontrol as
standard function





Spreading width up to 8 meter



Flip-up chute



Tarp cover and top screen

SPREADER FUNCTIONS

- ✓ A 12-volt motor is mounted inside a sealed weather-resistant enclosure, and requires no pulleys, sprockets, belts or chains.
- ✓ Vibrator prevents bridging and de-icing material from clogging by shaking the inverted Vee.
- ✓ The 65 mm stainless steel auger gives you an even flow of material to the spinner.
- ✓ Inverted-Vee helps reduce heavy start-up loads on the auger. All in stainless steel.
- ✓ Two-piece tarp mechanism, prevents spill off into truck bed when filling the spreader.
- ✓ Top screen prevents rocks and big material chunks from getting into the hopper.
- ✓ Flip-up stainless steel chute

OPTIONAL FEATURES

- + License plate kit and rear light
- + Beacon warning-light
- + LED-work light (red)
- + Rear camera
- + Pre-wet salt liquid kit; nozzles, pump, tank
- + Standlegs

OPTIONAL HTRACK™ SYSTEM

Track and manage all of your spreading devices and snowplows online on your computer, tablet or smartphone. The program shows treatment route on map, and spreading details like speed, GPS location, material used etc. With HTrack™ you can keep track of your expenses and get de-icing performance evidence for slip and fall injury claims. The spreading data can be summarized and generated as PDF reports.



The optional HTrack™ program transfers spreading data via mobile network

SPREADER SPECIFICATIONS

MODEL	ICESTRIKER STAINLESS STEEL
Total width	910 mm
Total length	1670 mm
Hopper length	1110 mm
Height	730 mm
Weight	120 kg
Capacity, water level	350 l
Capacity, rounded	380 l
Hopper construction	Stainless steel
Spreading width	1-8 m*
Spinner diameter	390 mm
Auger diameter	65 mm
Material	Sand, salt, gravel, mixes (max 8 mm Ø)
Power source	Electric 12V DC

* May vary depending on material

PRE-WET SYSTEM (OPTIONAL)

Spray volume	3-12 l/min
Liquid tank capacity	100 l
De-icing solutions	Anti- and de-icing liquids, water**

** Do not use petroleum or flammable liquids for the pre-wet system



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md