

COMPACTCUT 900 P/T

LISSMAC

CONSTRUCTION TECHNOLOGY

POWERFUL AND COMPACT FLOOR CUTTER FOR DRY CUTTING



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md


- No water required, cleaner surfaces, no further steps needed to prepare joints for grouting.
- Suited for fast preparation of joints, renovations and tight construction sites
- Electro- hydraulic lowering and raising of the saw blade with a threaded spindle with cutting depth indicator prevents damage to the saw blade
- Propulsion by hydrostatic gear drive guarantees smooth and controlled operation of the machine
- Smooth axle pivot steering for quick and easy moving and set-up without physical stress for the operator, as well as effortless cutting adjustments
- Torsion -resistant frame construction
- Optimal drive unit location allows for easy access for routine maintenance work (air filter, battery, oil and fuel filter)
- Parking brake and neutral gear comes as a standard feature
- Low center of gravity ensures a precise saw cut
- Integrated closed dry vacuum system VACUUM-DRY 100 for dust free cutting
- 7 rugged V-belts for optimal power transmission
- Height adjustable handles ensure ergonomic operation



COMPACTCUT 900 P/T



[1] Flush cutting blade guard



[2] Spot-light



[3] Warning flasher



Operator panel



ETOP

creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

TECHNICAL DATA	COMPACTCUT 900 P/T
cutting depth max.	125 mm
cutting depth setting	electrohydr. with depth gauge
saw blade Ø max.	400 mm
saw blade holder	25.4 mm
drive motor	Briggs+Stratton petrol 2 cyl.
output power max.	26 kW, 35 hp
saw blade speed	2130 1/min.
dimensions (L/W/H)	1600/800/1570 mm
weight	576 kg



DIAMOND TOOLS RECOMMENDATION

Asphalt	ASTP 703
---------	----------

FLOOR SAWS	NR.
COMPACTCUT 900 P/T without diamond blade, incl. blade guard 400 mm	1021713

ACCESSORIES	NR.
[1] COMPACTCUT 900 P/T - flush cutting blade guard 350 mm	1067441
COMPACTCUT 900 P/T - flush cutting shaft	1070390
[2] COMPACTCUT 900 P/T - spot-light LED 12 V	1040256
[3] COMPACTCUT 900 P/T - warning flasher	816002