

Placa compactoare reversibila




PCR160

Domenii de utilizare:
Compactare balast, agregate,
pamant pentru constructii civile,
industriale si infrastructura



Echipare standard: contor ce
afiseaza nr. ore functionare si
turatia motorului



Schimbarea acceleratiei si
directiei de compactare
tip heavy-duty
se face mecanic

Placa compactoare reversibila	PCR160-S	PCR160-H	PCR160-L
Tip motor	Subaru EX21	Honda GX160	Loncin
Combustibil	Benzina	Benzina	Benzina
Putere motor	7 cp	5.5 cp	9.0 cp
Volum rezervor	3.6 l	3.1 l	3.6 l
Frecventa vibratii	4000 vpm	3600 rpm	4000 rpm
Dimensiune talpa	700x520 mm		
Dimensiune extensie	700x85 mm		
Fora de compactare	30.5 kN		
Adancime max. de compactare	500 mm		
Eficienta compactare	570 m2/h		
Sistem schimb directie	Mecanic		
Viteza intrare	25 cm/s		
Greutate utilaj	162 kg	160 kg	162 kg
Dimensiuni (mm) L/I/h	1000x460x1020		



Disponibila cu talpa din otel cu extensii
sau din fonta



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md