

# Placa compactoare reversibila



## PCR320

Domenii de utilizare:

Compactare balastru, pamant, agregate pentru constructii civile, industriale si infrastructura



Echipare standard cu extensie talpa



PCR320-L  
Motor Lombardini diesel  
Pornire electrica (baterie inclusa)

Placa compactoare reversibila	PCR320-S	PCR320-L	PCR320-H
Tip motor	Subaru EX40	Lombardini 15 LD 350	Honda GX390
Combustibil	Benzina	Diesel	Benzina
Putere motor	14 cp	7.5 cp	13 cp
Volum rezervor	7 l	4.3 l	6.1 l
Frecventa vibratii	3750 vpm	3600 vpm	3600 vpm
Dimensiune talpa	890x640 mm		
Dimensiune extensie	890x85 mm		
Fora de compactare	38 kN	38 kN	38 kN
Adancime max. de compactare	900 mm	900 mm	900 mm
Eficienta compactare	650 m <sup>2</sup> /h	650 m <sup>2</sup> /h	650 m <sup>2</sup> /h
Sistem schimb directie	Mecanic	Mecanic	Mecanic
Viteza inaintare	35 cm/s	35 cm/s	35 cm/s
Greutate utilaj	305 kg	310 kg	305 kg
Dimensiuni (mm) L/l/h	1230/480/1400		



Echipare standard: contor ce afiseaza nr. ore functionare si turatia motorului



Schimbarea acceleratiei si directiei de compactare tip heavy-duty se face mecanic



**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chișinău, str. Uzinelor 90  
+ /373/ 67 707 707  
office@etop.md  
www.etop.md