

COMPACTCUT 401 E

LISSMAC

CONSTRUCTION TECHNOLOGY

ROBUST, HIGH-PERFORMANCE ELECTRIC JOINT CUTTER –
IDEAL FOR CUTTING WORK IN BUILDINGS



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ 373/ 67 707 707
office@etop.md
www.etop.md

- The LISSMAC electrofusion cutters operate quietly and are thus particularly suitable for cutting work on and in buildings
- The lowering and lifting of the saw blade is continuous by means of a threaded spindle, thus damage to the saw blade can be avoided.
- Optimum speed of the saw blade shaft.
- Saw hood foldable at the front for overcuts
- Excellent directional stability due to optimal centre of gravity of the machine to the blade
- Handles height adjustable and variably pluggable for ergonomic work
- Easily convertible from left to right cut in just a few simple movements
- Fork spray directly through the hood
- Optimum weight distribution on the front wheels ensures high tracking and sawing accuracy
- Adjustable depth of cut display
- Stable dipstick in H-shape
- Continuous saw blade shaft with V-belt drive
- Saw blade excavation via low-maintenance rocker design



[1] Flush cutting blade guard



Easily dismantled into 3 parts





ETOP

creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

TECHNICAL DATA	COMPACTCUT 401 E
cutting depth max.	320 mm
cutting depth setting	handwheel - threaded spindle
saw blade Ø max.	800 mm
saw blade holder	25.4 mm
saw blade fixing (flush cuts)	6 x M8 -TK125
drive motor	electric
output power max.	7,5 kW
voltage	400 V / 16 A
saw blade speed	1250 '/min.
left and right cut	yes
dimensions (L/W/H)	940/660/1210 mm
weight	161 kg

DIAMOND TOOLS RECOMMENDATION

Asphalt	ASW 11
Concrete	BSP 101 E

FLOOR SAWS	NR.
COMPACTCUT 401 E without diamond blade, incl. blade guard 800 mm	1069137
ACCESSORIES	NR.
[1] COMPACTCUT 401 E - flush cutting blade guard 800 mm	1065244