



- Increases the lifetime of the floor saw as no contaminated water vapour or dust can enter into the suction air of the drive motor

VACUUM-WET 100

- Can be adapted to any floor saw using the corresponding accessories, such as a saw blade protective hood with vacuum shoe
- Closed system which is mounted to a robust chassis and of course is driven by a Honda petrol or electric motor

VACUUM-WET 300

- Can be adapted to the floor saw MULTICUT 900 / 905 SGH using the corresponding accessories, such as a saw blade protective hood with vacuum shoe
- Closed system that is directly installed on the floor saw and driven by a hydraulic interface to the machine

VACUUM-WET 500

- Faster and easier attachment to the floor saw UNICUT 520 and UNICUT 600 with only two plug bolts
- All parts can be quickly removed for cleaning
- Simple emptying of the wet container using eccentric lever
- Wet container with fine hole Ø 5 mm sieve easy and quick to clean
- Hole sieve made completely of stainless steel (service life)
- Compact design with high ground clearance
- Closed system that is directly installed on the floor saw and driven by a hydraulic interface to the machine



VACUUM-WET 100 P



[1] VACUUM-WET 300



[2] VACUUM-WET 500



[3] Suction hose incl. floor nozzle



ETOP

creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

TECHNICAL DATA	VACUUM-WET 100	VACUUM-WET 300	VACUUM-WET 500
drive motor (VACUUM-WET 100 P)	petrol 9,6 kW	-	-
drive motor (VACUUM-WET 100 E)	electric 7,5 kW	-	-
container for coarse parts	-	25 l	25 l
sieve for coarse parts	-	Ø 5 mm	Ø 5 mm
required hydraulic supply	-	Q=40 l/min;130bar	Q=40 l/min;140bar
air delivery rate	1600 m ³ /h	1600 m ³ /h	2200 m ³ /h
water delivery rate	1250 l/h	1250 l/h	2450 l/h
power consumption		5 kW	9 kW
fresh water connection		GEKA-coupling, min. ¾", length max. 40 m	
waste water connection		GEKA-coupling, min. 1", length max. 40 m	
exhaust hose connection	Ø 100 mm, length max. 10 m	Ø 100 mm, length max. 10 m	Ø 100 mm, length max. 10 m
dimensions (L/W/H)	1120/700/1600 mm	750/575/1000 mm	600/900/1300 mm
total weight	196 kg (P); 222 kg (E)	140 kg	250 kg

SUCTION UNITS	NR.
VACUUM-WET 100 P - wet, incl. 5 m hose, Ø 100 mm	818167
VACUUM-WET 100 E - wet, incl. 5 m hose, Ø 100 mm	818175
[1] VACUUM-WET 300 - wet	818203
[2] VACUUM-WET 500 - wet	818204

ACCESSORIES	NR.
[3] VACUUM-WET 100 - suction hose incl. floor nozzle and 4 m hose, Ø 50 mm	818176