

LWSE 540

LIGHTWEIGHT, FLEXIBLE AND UNIVERSALLY APPLICABLE

LISSMAC

CONSTRUCTION TECHNOLOGY



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

- Safe and easy handling
- Perfect straight cuts
- Cutting depth adjustment
- Less straining for the operator compared to handheld saws
- Suitable for reinforced concrete and masonry
- Wide accessory range

Guide rails

- Extremely lightweight aluminium guide rail
- Direct wall mounting with the help of two plugs M12
- Robust design allows for opposite cuts
- Carriage is fixed on the rail system
- Integrated water level assures exact mounting
- Slotted mounting ring assures rapid and exact adjustment

Sawing system

- Patented mounting system of the sawing machine on the carriage
- Ensured safety even when sticking in the wall
- Stitching saw cuts are possible
- Overload protection: thermal overload protection, friction clutch, PRCD (Portable Residual Current Device)

Flush cut saw

- Aluminum saw blade guard
- Brush can easily be exchanged
- Complete flush guard kit comes as accessories kit



[1] Set of aluminium rail couplers



[2] Transport box



[3] Flush guard cut kit



ETOP

creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

TECHNICAL DATA	LWSE 540
cutting depth max.	115 mm / 165 mm / 210 mm
saw blade Ø max.	350 mm / 450 mm / 540 mm
saw blade holder	30 mm
output power max.	2.2 kW, 230 V
saw blade speed	2700 1/min.
weight saw head	14.6 kg
weight guide rail 1.3 m	6.6 kg
weight guide rail 2.3 m	9.9 kg

WALL SAW SYSTEM LWSE 540	NR.
LWSE 540 saw unit incl.	1043656
- guide rail 1,300 mm + carriage	
- guide rail 2,300 mm + carriage	
- transport box for saw unit	
- transport box for guide rails 1,300 mm	
- transport box for guide rails 2,300 mm	

ACCESSORIES	NR.
LWSE 540 - guide rail 1,300 mm + carriage with spacer plates 2 x T=2 mm / T=3 mm / T=5 mm	1043657
LWSE 540 - guide rail 2,300 mm + carriage with spacer plates 2 x T=2 mm / T=3 mm / T=5 mm	1043658
[1] LWSE 540 - set of aluminium rail couplers	1043659
LWSE 540 - transport box for saw unit	1043660
[2] LWSE 540 - transport box for guide rails 1,300 mm	1043661
[2] LWSE 540 - transport box for guide rails 2,300 mm	1043662
[3] LWSE 540 - flush guard cut kit (flush guard Ø 540 mm + 3 pcs flush blade flange)	1043663