

LWSE 800 / LWSE 1200

LISSMAC

CONSTRUCTION TECHNOLOGY

ELECTRIC WALL SAWS FOR UNIVERSAL APPLICATIONS AND EVERYDAY USE ON THE CONSTRUCTION SITE



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+373/67 707 707
office@etop.md
www.etop.md

LWSE 800

- Both installation and dislocation are realized in a glimpse
- Integrated design with only one cable and one hose
- Combined with the perfected electronic feed control the power of the extremely compact motor delivers an unmatched cutting performance within the 16A range
- Optimized system-specific blade guard and light tracks
- Handy radio remote control

LWSE 1200

- The pioneering drive concept enables the combination of extreme reliability and optimum performance with low service requirements and reduced service costs
- 4 application options by means of an expandable system: wall sawing/wire sawing/circular wire sawing/drilling
- Simple assembly and disassembly due to lightweight and compact system components
- Innovative, powerful and low-maintenance electric motor without transmission
- Optimised remote control for greater mobility and increased safety
- Lightweight control unit enables use in the 16 and 32 A range



LWSE 800



LWSE 1200



[1] Rotary rail support



[2] Electric control unit+ radio remote control



[3] Blade guard



[4] V-Track feet alu



ETOP

creat să reziste

Republica Moldova, MD-2023
 mun. Chișinău, str. Uzinelor 90
 + /373/ 67 707 707
 office@etop.md
 www.etop.md

TECHNICAL DATA	LWSE 800	LWSE 1200
cutting depth max.	335 mm	520 mm
saw blade Ø max.	825 mm	1200 mm
free detachable up to Ø	650 mm	800 mm
saw blade holder	60 mm / 25,4 mm	60 mm
blade flange mounting	central screw	quick-release flange
saw blade fixing (flush cuts)	6 countersunk head screws, TK 90 mm	6 countersunk head screws, TK 130 mm
motor	water-cooled	water-cooled, without gearbox
output power max. at 16 A	9 kW	8 kW
output power max. at 32 A	-	17 kW
voltage	400 V / 16 A	400 V
frequency	50 Hz / 60 Hz	50 Hz / 60 Hz
protection class	IP 65	IP 67
weight sawing body	30 kg	-
weight wall saw head (complete)	-	22 kg
weight drive	-	15 kg

WALL SAW SYSTEM LWSE 800	NR.
LWSE 800 wall saw incl. feed motors	1042127
LWSE 800 - track cpl. 700mm	1042111
LWSE 800 - track cpl. 1100mm	1042110
LWSE 800 - track cpl. 2200mm	1042113
[1] LWSE 800 - rotary rail support (recommended: 3 pieces)	1042108
LWSE 800 - track stop (recommended: 2 pieces)	1042109
LWSE 800 - blade guard All-In-One 750 mm	1042107
LWSE 800 - transport trolley	1042112

WALL SAW SYSTEM LWSE 1200	NR.
LWSE 1200 wall saw incl. feed motors	1042104
LWSE 1200 - electric main drive motor 400 V/50 Hz	1042102
[2] LWSE 1200 - electric control unit 400 V/50 Hz incl. radio remote control	1042105
LWSE 1200 - transport trolley	1042087
[3] LWSE 1200 - blade guard 1000 mm 3 parts All-In-One	1042095
LWSE 1200 - VAS G Track / 1100 mm / alu	1042090
LWSE 1200 - VAS G Track / 2200 mm / alu	1042088
LWSE 1200 - track connector for VAS and VS tracks	1042075
[4] LWSE 1200 - V-Track feet alu, flat (recommended: 3 pieces)	1042045

ACCESSORIES	NR.
LWSE 1200 - track connector for VAS and VS tracks	1042075
LWSE 1200 - blade flange ST compl.	1042086
[3] LWSE 1200 - blade guard 800 mm 3 parts All-In-One	1042094
[3] LWSE 1200 - blade guard 1000 mm 3 parts All-In-One	1042095
[3] LWSE 1200 - blade guard 1200 mm 3 parts All-In-One	1042096
[4] LWSE 1200 - V-Track feet alu, flat	1042045