



LWSH 1201

- The extremely sturdy and proven design ensures high reliability and cutting accuracy
- In conjunction with hydraulic drives with outputs of up to 20 kW, blade diameters of up to maximum 1200 mm can be used.
- Robust saw head with standard hydraulic motors
- Blade guard for normal and flush cutting
- Slide guide with ergonomic locking system and fine adjustment

Design

- GR2 hydraulic motor with quick-change device
- Swivel arm, can be rotated by 360°
- Power transmission in swivel arm via toothed belt
- Carriage controlled using bronze guide



LWSH 1201

LWSH 1600

- Use of the quick-separation flange on the swivel arm provides simple, fast blade replacement and facilitates use in flush cutting applications
- Innovative feed motors ensure fast cutting
- In conjunction with hydraulic drives with outputs of up to 25 W, blade diameters of up to maximum 1600 mm can be used
- Wall saw head constructed from high-strength aluminium base alloy, gear swivel arm and roller guides
- Gear swivel arm with quick separation flange mounting
- Wall saw head can be mounted quickly and easily

Design

- GR2 hydraulic motor with quick-change device
- Swivel arm, can be rotated by 360°
- Power transmission in swivel arm via gear wheel
- Carriage guided by rollers



LWSH 1600



[1] Blade guard



[2] V-Track feet alu



Drive



ETOP

creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

TECHNICAL DATA	LWSH 1201	LWSH 1600
cutting depth max.	510 mm	700 mm
saw blade Ø max.	1200 mm	1600 mm
free detachable up to	900 mm	825 mm
saw blade holder	60 mm	60 mm
blade flange mounting	central screw	quick-release flange
saw blade fixing (flush cuts)	6 countersunk head screws, TK 130 mm	6 countersunk head screws, TK 130 mm
weight incl. drive motor and 2 feed motors	34 kg	29 kg
weight with 2 feed motors only	27 kg	24 kg

WALL SAW SYSTEM LWSH 1201	NR.
LWSH 1201 wall saw	1042092
LWSH 1201 - motor complete B/S 22 ccm / FD	1042061
[1] LWSH 1201 - blade guard 1000 mm 3 parts All-In-One	1042095
LWSH 1201 - VAS G Track / 1100 mm / alu	1042090
LWSH 1201 - VAS G Track / 2200 mm / alu	1042088
[2] LWSH 1201 - V-Track feet alu, flat (recommended: 3 pieces)	1042045
LWSH 1201 - Pressure relief valve FD	1042074

WALL SAW SYSTEM LWSH 1600	NR.
LWSH 1600 Wandsäge	1042089
LWSH 1600 - motor complete B/S 22 ccm / FD	1049394
[1] LWSH 1600 - blade guard 1000 mm 3 parts All-In-One	1042095
LWSH 1600 - VAS G Track / 1100 mm / alu	1042090
LWSH 1600 - VAS G Track / 2200 mm / alu	1042088
[2] LWSH 1600 - V-Track feet alu, flat (recommended: 3 pieces)	1042045
LWSH 1600 - Pressure relief valve FD	1042074
LWSH 1600 - quick-change set for motors Gr. 2	1042047

ACCESSORIES	NR.
LWSH 1201 - 1 piece bronze guide complete	1042048
LWSH 1201 - flush cutting flange	1042056
LWSH 1201 - tooth belt	1042046
[1] LWSH 1201 / 1600 - Blade guard 800 mm 3 parts All-In-One	1042094
[1] LWSH 1201 / 1600 - Blade guard 1000 mm 3 parts All-In-One	1042095
[1] LWSH 1201 / 1600 - Blade guard 1200 mm 3 parts All-In-One	1042096
LWSH 1600 - blade flange ST complete	1042086
LWSH 1600 - blade guard 1600 mm 2 parts	1042081
LWSH 1600 - blade guard holder 2 parts for bolt	1042071

MOTORS	NR.
LWSH 1201 - motor complete B/S 16 ccm / FD	1042059
LWSH 1201 - motor complete B/S 18 ccm / FD	1042060
LWSH 1600 - motor complete B/S 16 ccm / FD	1049392
LWSH 1600 - motor complete B/S 18 ccm / FD	1049393
LWSH 1201 / 1600 - quick-change set for motors size 2	1042047