

Placa compactoare reversibila

PCR255

Domenii de utilizare:

Compactare balast, agregate, pamant pentru constructii civile, industriale si infrastructura

PCR255-L
Motor diesel Lombardini
Pornire electrica (baterie inclusa)



Echipe standard: contor ce afiseaza nr. ore functionare si turatia motorului

Schimbarea acceleratiei si directiei de compactare tip heavy-duty se face mecanic



Placa compactoare reversibila	PCR255-L	PCR255-LK	PCR255-H
Tip motor	Loncin G390F	Lombardini/Kohler 15 LD 350	Honda GX390
Combustibil	Benzina	Diesel	Benzina
Putere motor	13 cp	7,5 cp	13 cp
Volum rezervor	6,1 l	4,3 l	6,1 l
Frecventa vibratii	3600 vpm		
Dimensiune talpa	820x480 mm		
Dimensiune extensie	820x85 mm		
Forta de compactare	38 kN		
Adancime max. de compactare	900 mm		
Eficienta compactare	650 m ² /h		
Sistem schimb directie	Mecanic		
Viteza intrare	35 cm/s		
Greutate utilaj	255 kg	270 kg	255 kg
Dimensiuni (mm) L/l/h	1.030/480/1.160		



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md