

Generator de curent stationar cu automatizare la pornire



Generator	BIAA40
Putere max. generator	40 kVA / 32 kW
Putere generator continua	36 kVA / 29 kW
Voltaj	400 / 230 V
Frecventa	50 Hz
Factor de putere	0,8
Panou ATS	Inclus in standard
Regulator de tensiune	AVR
Motor	AYD4NS32
Demaraj	Electric
Turatie motor	1.500 rpm
Nr. cilindri motor	4 vertical in linie
Aspirare aer	Normala
Preincalzire motor	Inclus in standard
Racire motor	Apa
Capacitate lichid racire	14,5 l
Carburant	Motorina
Consum sub 50% sarcina	4,2 l/h
Capacitate rezervor	105 l
Capacitate rezervor ulei	12 l
Numar poli	4
Tip alternator	Autoexcitatie, fara perii
Regulator turatie motor	Mecanic
Precizia tensiunii de iesire	± 1%
Clasa izolare	H
Clasa protectie	IP23
Greutate	1.125 kg
Dimensiuni LxIxh (mm)	2.100 x 1.000 x 1.570

Model: BIAA40



Controller ALM 929



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90, of. 207
+ /373/ 67 707 707
office@etop.md
www.etop.md