

# Generator de curent stationar cu automatizare la pornire



| Generator                    | SKD25S              |
|------------------------------|---------------------|
| Putere max. generator        | 25.0 kVA / 19.8 kW  |
| Putere generator continua    | 22.5 kVA / 18.0 kW  |
| Voltaj                       | 400 / 230 V         |
| Frecventa                    | 50 Hz               |
| Factor de putere             | 0,8                 |
| Amperaj                      | 32,4 A              |
| Panou ATS                    | Inclus in standard  |
| Motor                        | YS490D              |
| Putere motor                 | 21 cp               |
| Turatie motor                | 1.500 rpm           |
| Nr. cilindri motor           | 4 vertical in linie |
| Aspirare aer                 | Normala             |
| Preincalzire motor           | Inclus in standard  |
| Racire motor                 | Lichid racire       |
| Capacitate lichid racire     | 5,2 l               |
| Carburant                    | Motorina            |
| Consum combustibil           | ≤ 235 g / kW / h    |
| Autonomie la 70% putere      | 30 ore              |
| Capacitate rezervor          | 86 l                |
| Tip ulei                     | 15W40               |
| Capacitate rezervor ulei     | 12 l                |
| Consum maxim de ulei         | 0,25 %              |
| Numar poli                   | 4                   |
| Regulator de tensiune        | AVR                 |
| Regulator turatie motor      | Mecanic             |
| Precizia tensiunii de ieşire | ± 1%                |
| Nivel zgomot la 7 metri      | 80 dB               |
| Greutate                     | 669 kg              |
| Dimensiuni LxIxh (mm)        | 1.950 x 900 x 1.050 |

**Model: SKD25S**



Dotare standard panou pentru automatizare la pornire tip ATS-M

Optional prize pe panoul de comanda:

1 x 400V 63A

1 x 400V 32A

1 x 230V 16A

Protectie generator IP32

Temperatura de lucru -15° + 70°C

Temperatura depozitare -30°C +80°C



**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chişinău, str. Uzinelor 90, of. 207  
+ /373/ 67 707 707  
office@etop.md  
www.etop.md