

# Generator de curent stationar cu automatizare la pornire



| Generator                    | BIAA82                    |
|------------------------------|---------------------------|
| Putere max. generator        | 82 kVA / 66 kW            |
| Putere generator continua    | 75 kVA / 60 kW            |
| Voltaj                       | 400 / 230 V               |
| Frecventa                    | 50 Hz                     |
| Factor de putere             | 0,8                       |
| Panou <b>ATS</b>             | Inclus in standard        |
| Regulator de tensiune        | <b>AVR</b>                |
| Motor                        | AYD4TS41E                 |
| Demaraj                      | Electric                  |
| Turatie motor                | 1.500 rpm                 |
| Nr. cilindri motor           | 4 vertical in linie       |
| Aspirare aer                 | Turbocharger/Intercooler  |
| Preincalzire motor           | Inclus in standard        |
| Racire motor                 | Apa                       |
| Capacitate lichid racire     | 17 l                      |
| Carburant                    | Motorina                  |
| Consum sub 50% sarcina       | 8 l/h                     |
| Capacitate rezervor          | 140 l                     |
| Capacitate rezervor ulei     | 12 l                      |
| Numar poli                   | 4                         |
| Tip alternator               | Autoexcitatie, fara perii |
| Regulator turatie motor      | Electronic                |
| Precizia tensiunii de iesire | $\pm 1\%$                 |
| Clasa izolare                | H                         |
| Clasa protectie              | IP23                      |
| Greutate                     | 1.275 kg                  |
| Dimensiuni Lxlxh (mm)        | 2.350 x 1.100 x 1.730     |

Model: **BIAA82**



**Controller ALM 929**



**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chișinău, str. Uzinelor 90, of. 207  
+ /373/ 67 707 707  
office@etop.md  
www.etop.md