



NOWOŚĆ



Power generator F 4001 iS

Nr art. 35772

Characteristic

- Stable frequency 50 Hz
- Inverter technology
- Voltage stabilization $\pm 1\%$
- Low level of THD $\leq 3\%$
- Supersilent 96 dB(A)
- Weight only 28 kg
- Fuel saving function reduce engine speed at low load
- Possibility of synchronization two units F 4001 iS
- Battery charger

Technical parameters

Frequency	50 Hz
Voltage	230 V
Maximum power	3,3 kW
Nominal power	3,0 kW
Prime current	13 A
Engine	Rato
Model	R 185 Vi
Capacity	185 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	0,5 L
Starting system	Manual
Fuel	Petrol
Fuel tank	5,5 L
Consumption (load 50/100%)	0,97 / 1,54 L / h
Noise level Lwa	96 dB(A)
Weight	28 kg
Length	561 mm
Width	381 mm
Height	516 mm

Standard equipment

- 2 Sockets 230 V 16 A
- USB Socket
- Socket and cables for battery charging 12 V 8,3 A
- Overload sygnalization
- Overload protection
- Low oil warning diode

Optional and service equipment

- Exhaust hose Nr art. 15876
- Exhaust adapter Nr art. 37087
- Synchronization cables for two generators F4001 iS Nr art. 26790
- Service kit (air filter, spark plug, engine oil) Nr art. 33643

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive
- **2014/30/UE**
EC Directive



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md