



Power generator

F 5001

Nr art. 36101

Characteristic

- Regulația napięcia $\pm 5 \%$
- Low level of THD $\leq 6 \%$
- Shortcut starting current 250 %
- Alternator insulation class H
- Alternator protection IP 23

Technical parameters

Frequency	50 Hz
Voltage	230 V
Maximum power	4,2 kW
Nominal power	3,8 kW
Prime current	16,5 A
Engine	Rato
Model	R300
Capacity	301 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,1 L
Starting system	Manual
Fuel	Petrol
Fuel tank	5,4 L
Consumption (load 50/100%)	2,2 L / h
Noise level Lwa	97 dB(A)
Weight	54 kg
Length	650 mm
Width	520 mm
Height	490 mm

Standard equipment

- 2 sockets 230 V 16 A
- Overload protection
- Oil level sensor

Optional and service equipment

- Hourmeter Nr art. 23300
- Transportation set Nr art. 24429
- Service kit (air filter, spark plug, engine oil) Nr art. 35110

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive
- **2014/30/UE**
EC Directive



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md