



Power generator

F 8000 TRA

Nr art. 35588

Characteristic

- Cyfrowa regulacja napięcia $\pm 1,5\%$ na każdej fazie
- Low level of THD $\leq 6\%$
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP 23
- Autonomy (at 75 % load) 15,5h
- Ready for manual and automatic operation

Technical parameters

Frequency	50 Hz
Voltage	400 / 230 V
Power 3~ max / nom.	7,7 kVA / 7,0 kVA (cos ϕ 0,8)
Prime current 3~	10,1 A
Power 1~ max / nom.	3,9 kW / 3,5 kW
Prime current 1~	15,2 A

Engine	Rato
Model	R 420
Capacity	420 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,1 L
Starting system	Manual + electric
Fuel	Petrol
Fuel tank	45 L
Consumption (load 75%)	2,9L / h
Noise level Lwa	99 dB(A) do zabudowy

Weight	95 kg
Length	790 mm
Width	580 mm
Height	650 mm

Standard equipment

- AVR
- Socket 400 V 16 A
- Socket 230 V 16 A
- Overload protection
- Oil level sensor
- Silencer with exhaust adapter
- Battery
- Connection for ATS panel

Optional and service equipment

- Exhaust hose
- Hourmeter
- Transportation set
- Service kit
- (air filter, spark plug, engine oil)
- ATS panel

Norms and Directives

- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive
- **2014/30/UE**
EC Directive



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md