



# Power generator **F 9000 TE**

Nr art. 29821

## Characteristic

- Regulacja napięcia  $\pm 6\%$
- Low level of THD  $< 4\%$
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP 23
- Autonomy (at 75 % load) 15,5h

## Technical parameters

<b>Frequency</b>	<b>50 Hz</b>
<b>Voltage</b>	<b>400 / 230 V</b>
<b>Power 3~ max / nom.</b>	<b>8,3 kVA / 7,5 kVA (cos <math>\phi</math> 0,8)</b>
<b>Prime current 3~</b>	<b>10,9 A</b>
<b>Power 1~ max / nom.</b>	<b>5,7 kW / 5,2 kW</b>
<b>Prime current 1~</b>	<b>22,6 A</b>

Engine	Rato
Model	R 420
Capacity	420 cm <sup>3</sup>
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,1 L
Starting system	Manual + electric
Fuel	Petrol
Fuel tank	45 L
Consumption (load 75%)	2,9 L / h
Noise level Lwa	99 dB(A)

Weight	107 kg
Length	790 mm
Width	580 mm
Height	650 mm

## Standard equipment

- Socket 400 V 16 A
- Socket 230 V 16 A
- Overload protection
- Oil level sensor
- Silencer with exhaust adapter
- Battery

## Optional and service equipment

- Exhaust hose Nr art. 15876
- Hourmeter Nr art. 23300
- Transportation set Nr art. 34995
- Service kit  
(air filter, spark plug, engine oil) Nr art. 35447

## Norms and Directives

- **2006/42/WE**  
Machinery Directive
- **2014/35/UE**  
Low Voltage Directive
- **2014/30/UE**  
EC Directive



**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chișinău, str. Uzinelor 90  
+ /373/ 67 707 707  
office@etop.md  
www.etop.md