



Power generator F 9000 TRA

Nr art. 29823

Characteristic

- Cyfrowa regulacja napięcia $\pm 1,5\%$ na każdej fazie
- Low level of THD $< 6\%$
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP 23
- Autonomy (at 75 % load) 15,5h
- Ready for manual and automatic operation

Technical parameters

Frequency	50 Hz
Voltage	400 / 230 V
Power 3~ max / nom.	8,3 kVA / 7,5 kVA (cos ϕ 0,8)
Prime current 3~	10,9 A
Power 1~ max / nom.	5,0 kW / 4,5 kW
Prime current 1~	19,6 A

Engine	Rato
Model	R 420
Capacity	420 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,1 L
Starting system	Manual
Fuel	Petrol
Fuel tank	45 L
Consumption (load 75%)	2,9 L / h
Noise level Lwa	99 dB(A)

Weight	101 kg
Length	790 mm
Width	580 mm
Height	650 mm

Standard equipment

- AVR
- Socket 400 V 16 A
- Socket 230 V 16 A
- Overload protection
- Oil level sensor
- Silencer with exhaust adapter
- Battery
- Connection for ATS panel

Optional and service equipment

- Exhaust hose
 - Hourmeter
 - Transportation set
 - Service kit (air filter, spark plug, engine oil)
- Nr art. 15876
Nr art. 23300
Nr art. 34995
Nr art. 35447

Norms and Directives

- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive
- **2014/30/UE**
EC Directive



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md