



Power generator FH 7001

Nr art. 37018

Characteristic

- Voltage stabilization +5 -10 %
- Low level of THD $\leq 6\%$
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP 23
- Full single phase power output socket 32 Amps

Technical parameters

Frequency	50 Hz
Voltage	230 V
Maximum power	6,2 kW
Nominal power	5,6 kW
Prime current	24,3 A
Engine	Honda
Model	GX 390
Capacity	389 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,1 L
Starting system	Manual
Fuel	Petrol
Fuel tank	6,1 L
Consumption (load 50/100%)	2,7 L / h
Noise level Lwa	97 dB(A)
Weight	69 kg
Length	790 mm
Width	580 mm
Height	505 mm

Standard equipment

- Socket 230 V 16 A
- Socket 230 V 32 A
- Overload protection
- Oil level sensor

Optional and service equipment

- Exhaust hose Nr art. 15876
- Exhaust adapter Nr art. 10118
- Hourmeter Nr art. 23300
- Transportation set Nr art. 34994
- Service kit Nr art. 16582
(air filter, spark plug, engine oil)

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive
- **2014/30/UE**
EMC Directive



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md