



Power generator **FH 8000 R**

Nr art. 36768

Characteristic

- Cyfrowa Voltage stabilization $\pm 1,5\%$ na každej fazie
- Low level of THD $\leq 6\%$
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP 23

Technical parameters

Frequency	50 Hz
Voltage	400 / 230 V
Power 3~ max / nom.	7,7 kVA / 7,0 kVA (cos ϕ 0,8)
Prime current 3~	10,1 A
Power 1~ max / nom.	3,9 kW / 3,5 kW
Prime current 1~	15,2 A

Engine	Honda
Model	GX 390
Capacity	389 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,1 L
Starting system	Manual
Fuel	Petrol
Fuel tank	6,1 L
Consumption (load 75%)	2,7 L / h
Noise level Lwa	97 dB(A)

Weight	70 kg
Length	790 mm
Width	580 mm
Height	505 mm

Standard equipment

- AVR
- Socket 400 V 16 A
- Socket 230 V 16 A
- Overload protection
- Oil level sensor

Optional and service equipment

- Exhaust hose Nr art. 15876
- Exhaust adapter Nr art. 10118
- Hourmeter Nr art. 23300
- Transportation set Nr art. 34994
- Service kit
(air filter, spark plug, engine oil) Nr art. 16582

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive
- **2014/30/UE**
EMC Directive



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md