



Power generator FH 9000 TE

Nr art. 37048

Characteristic

- Voltage stabilization $\pm 4\%$
- Low level of THD $< 4\%$
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP 23
- Autonomy (at 75 % load) 16,7 h
- Lowered noise level from 97 to 96 dB(A)
- Frame diameter 38 mm

Technical parameters

Frequency	50 Hz
Voltage	400 / 230 V
Power 3~ max / nom.	8,7 kVA / 7,8 kVA (cos ϕ 0,8)
Prime current 3~	11,3 A
Power 1~ max / nom.	5,7 kW / 5,2 kW
Prime current 1~	22,6 A

Engine	Honda
Model	GX 390
Capacity	389 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,1 L
Starting system	Manual + electric
Fuel	Petrol
Fuel tank	45 L
Consumption (load 75%)	2,7 L / h
Noise level Lwa	96 dB(A)

Weight	109 kg
Length	790 mm
Width	580 mm
Height	650 mm

Standard equipment

- Socket 400 V 16 A
- Socket 230 V 16 A
- Overload protection
- Oil level sensor
- Silencer with exhaust adapter
- Battery

Optional and service equipment

- Exhaust hose Nr art. 15876
- Hourmeter Nr art. 23300
- Transportation set Nr art. 34995
- Service kit Nr art. 23294
(air filter, spark plug, engine oil)

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive
- **2014/30/UE**
EMC Directive



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md