



Power generator

FH 9540 TRA

Nr art. 37062

Characteristic

- Digital voltage regulation $\pm 2\%$ on three phases
- Low level of THD $\leq 4\%$
- Shortcut starting current $> 350\%$
- Alternator insulation class H
- Alternator protection IP 54
- Full single phase power output socket 32 Amps
- Autonomy (at 75 % load) 16,7 h
- Lowered noise level from 97 to 96 dB(A)
- Frame diameter 38 mm

Technical parameters

Frequency	50 Hz
Voltage	400 / 230 V
Power 3~ max / nom.	8,1 kVA / 7,3 kVA (cos ϕ 0,8)
Prime current 3~	10,6 A
Power 1~ max / nom.	5,5 kW / 5,0 kW
Prime current 1~	19,6 A

Engine	Honda
Model	GX 390
Capacity	389 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,1 L
Starting system	Manual + electric
Fuel	Petrol
Fuel tank	45 L
Consumption (load 75%)	2,7 L / h
Noise level Lwa	96 dB(A)

Weight	124 kg
Length	790 mm
Width	580 mm
Height	765 mm

Standard equipment

- AVR
- Socket 400 V 16 A
- Socket 230 V 32 A
- Socket 230 V 16 A
- Overload protection
- Oil level sensor
- Silencer with exhaust adapter
- Hourmeter
- Battery

Optional and service equipment

- Exhaust hose
 - Transportation set
 - Service kit (air filter, spark plug, engine oil)
 - ATS panel
- Nr art. 15876
Nr art. 34995
Nr art. 23294
Nr art. 30312

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md