



Power generator

FV 11001 TRA

Nr art. 37127

Characteristic

- Voltage stabilization $\pm 1\%$
- Low level of THD $< 4\%$
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP 23
- Full single phase power output socket 63 Amps
- Autonomy (at 75 % load) 9,2 h
- Outdoor operation without enclosure - Noise level Lwa 97 dB(A)
- Frame diameter 38 mm

Technical parameters

Frequency	50 Hz
Voltage	230 V
Maximum power	11,0 kW
Nominal power	10,0 kW
Prime current	43,5 A
Engine	Vanguard
Model	3854
Capacity	627 cm ³
Cooling	Air
Cylinder	2
Stroke	4
Oil volume	1,7 L
Starting system	Manual + electric
Fuel	Petrol
Fuel tank	45 L
Consumption (load 50/100%)	4,9 L / h
Noise level Lwa	97 dB(A)
Weight	133 kg
Length	790 mm
Width	580 mm
Height	765 mm

Standard equipment

- AVR
- Socket 230 V 16 A
- Socket 230 V 63 A
- Overload protection
- Oil pressure sensor
- Silencer with exhaust adapter
- Battery
- Connection for ATS panel
- Hourmeter

Optional and service equipment

- Exhaust hose Nr art. 15876
- Transportation set Nr art. 28784
- Service kit
(air filter, spark plug, engine oil) Nr art. 16579
- ATS panel Nr art. 30310

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md