



Power generator

FV 17001 TRA

Nr art. 37147

Characteristic

- Voltage stabilization $\pm 2\%$
- Low level of THD $\leq 6\%$
- Shortcut starting current 400 %
- Alternator insulation class H
- Alternator protection IP 23
- Autonomy (at 75 % load) 6,9 h
- Frame diameter 38 mm
- Ready for manual and automatic operation

Technical parameters

| | |
|----------------------------|---------------------|
| Frequency | 50 Hz |
| Voltage | 230 V |
| Maximum power | 16,5 kW |
| Nominal power | 14,9 kW |
| Prime current | 64,8 A |
| Engine | Vanguard |
| Model | 5434 |
| Capacity | 896 cm ³ |
| Cooling | Air |
| Cylinder | 2 |
| Stroke | 4 |
| Oil volume | 2,3 L |
| Starting system | Electric |
| Fuel | Petrol |
| Fuel tank | 45 L |
| Consumption (load 50/100%) | 6,5 L / h |
| Noise level Lwa | 100 dB(A) |
| Weight | 168 kg |
| Length | 900 mm |
| Width | 580 mm |
| Height | 890 mm |

Standard equipment

- AVR
- Socket 230 V 16 A
- Socket 230 V 63 A
- Overload protection
- Oil pressure sensor
- Silencer with exhaust adapter
- Battery
- Connection for ATS panel
- Hourmeter

Optional and service equipment

- Exhaust hose Nr art. 15876
- Transportation set Nr art. 28784
- Service kit
(air filter, spark plug, engine oil) Nr art. 16580
- ATS panel Nr art. 30313

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md