



DESIGN AND PERFORMANCES ARC 1000®

MAX. WORKING WIDTH	1,000 mm Note: Lower working width is available by installation of less nozzles in the 1,000 mm cleaning head.
MAX. HIGH PRESSURE PERFORMANCE	2,500 / 3,000 bar
TANK VOLUME	13 m ³ (enlargeable on customer request)
MAX. PUMP PERFORMANCE	29 l/min Note: Technical performance limit of the most powerful pump. Other pumps available as per customer request.
SPEED DURING OPERATION	3 – 80 m/min (0.18 – 4.80 km/h) steplessly adjustable
ROTATION OF NOZZLES	0 – 2,500 rpm steplessly adjustable
RUBBER REMOVAL PERFORMANCE	Low layer removal (up to 2 mm): up to 2,800 m ² /h Middle layer removal (up to 4 mm): up to 1,200 m ² /h High layer removal (over 5 mm): up to 900 m ² /h
LINEAR PAINT REMOVAL PERFORMANCE	2,800 – 4,400 [*] linear m/h [*] Applicable for 1 layer of paint (standard thickness of 0.8 mm)
THERMOPLASTIC REMOVAL PERFORMANCE	2,400 – 4,000 linear m/h Thermoplastic spray removal (up to 0.8 mm) Thermoplastic flat line removal (up to 5 mm) Thermoplastic dot line removal (up to 5 mm)
POSSIBLE CLEANING OPTIONS	11

[Contact Us](#)



The surface cleaner in working position



Even the expansion joint material has not been destroyed



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md