



DESIGN AND PERFORMANCES ARC 2400®

MAX. WORKING WIDTH	2,400 mm Note: Lower working width is available by installation of less nozzles in the 3 of 800 mm cleaning heads.
MAX. HIGH PRESSURE PERFORMANCE (operating / technical limit)	2,500 / 3,000 bar
TANK VOLUME (Standard)	17m ³
MAX. PUMP PERFORMANCE	72 l/min Note: Technical performance limit of the most powerful pump. Other pumps available as per customer request.
SPEED DURING OPERATION	3 – 80 m/min (0.18 – 4.80 km/h) steplessly adjustable
ROTATION OF NOZZLES	0 – 2,500 rpm steplessly adjustable
RUBBER REMOVAL PERFORMANCE	Low layer removal (up to 2 mm): 4,800 – 5,700 m ² / hour Middle layer removal (up to 4 mm): 2,200 – 3,200 m ² / hour High layer removal (over 5 mm): 1,200 – 2,100 m ² / hour
LINEAR PAINT REMOVAL PERFORMANCE	3,800 – 5,800* linear meters / hour * Applicable for 1 layer of paint (standard thickness of 0.8 mm).
THERMOPLASTIC REMOVAL PERFORMANCE	3,300 – 5,300 linear meters / hour Thermoplastic spray removal (up to 0.8 mm) Thermoplastic flat line removal (up to 5 mm) Thermoplastic dot / line removal (up to 5 mm)
POSSIBLE CLEANING OPTIONS	5

Contact Us



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md