

DESIGN AND PERFORMANCES ARC 3000®

MAX. WORKING WIDTH	3,000 mm
MAX. HIGH PRESSURE PERFORMANCE (operating / technical limit)	2,500 / 3,000 bar
TANK VOLUME (Standard)	38 m ³
MAX. PUMP PERFORMANCE	88 l/min
SPEED DURING OPERATION	3 – 80 m/min (0.18 – 4.80 km/h) steplessly adjustable
ROTATION OF NOZZLES	0 – 2,500 rpm steplessly adjustable
RUBBER REMOVAL PERFORMANCE	Low layer removal (up to 2 mm): up to 6,000 m ² / hour Middle layer removal (up to 4 mm): up to 3,800 m ² / hour High layer removal (over 5 mm): up to 2,500 m ² / hour
LINEAR PAINT REMOVAL PERFORMANCE	2,800 – 4,400* linear m/h * Applicable for 1 layer of paint (standard thickness of 0.8 mm).
THERMOPLASTIC REMOVAL PERFORMANCE	2,400 – 4,000 linear m/h Thermoplastic spray removal (up to 0.8 mm) Thermoplastic flat line removal (up to 5 mm) Thermoplastic dot line removal (up to 5 mm)
POSSIBLE CLEANING OPTIONS	5

Contact Us



Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md