



## DESIGN AND PERFORMANCES OSC 5000

### CHASSIS

LADOG, 4x4, 84 kW engine, wheelbase 2,800 mm, 4 wheels steerable with hydrostatic gear and all needed PTO's

### AVERAGE CLEANING RESULTS:

Cleaning of large areas: Ø 2,000 m<sup>2</sup>/h  
Oil Spillage Removal: Ø 1,200 m<sup>2</sup>/h

### HIGH-PRESSURE PUMP

P max 250 bar (optional 300 bar) Q max 38 l/min

### TANK VOLUME

Fresh water tank 1,000 l – stainless steel, waste water tank 1,500 l – stainless steel

### SPEED DURING OPERATION

3 – 80 m/min (0.18 – 4.80 km/h)  
steplessly adjustable

### ROTATION OF NOZZLES

0 – 1,400 rpm  
steplessly adjustable for every cleaning device

### MAX. WORKING WIDTH

1,200 mm

### SUCTION / AIR BLOWER

19 kW

[Contact Us](#)



**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chişinău, str. Uzinelor 90  
+ /373/ 67 707 707  
office@etop.md  
[www.etop.md](http://www.etop.md)