

MIXER SPRINTER

EWI

Continuous mixing pump | reference : 910000100A



Compact continuous mixing pump, with reduced weight and size, easy to disassemble into 4 sections for simplified transport.

Ideal for a wide range of powder products, lime-, plaster- and cement-based surface coatings. This pump is also ideal for filling joints, resurfacing works, applying adhesives, interior and exterior finishes.

TECHNICAL DATA

Hopper capacity	70 L
Power supply	230 V~ 50 Hz
Motor thermal protection	yes
Variable speed	yes
Water pressure booster	yes
Flow meter	Digital display
Water shortage safety device	yes
Integrated compressor (cat. C5)	8021022700
Spraying flow rate	8 to 26 L/min*
Max. spraying distance	40 meters*
Loading height	102 cm
Dimensions (l x w x h)	98 x 72 x 153 cm
Weight	145 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 20 LM neoprene 3x4 power cord with plug
- Mixer spray lance for glue
- Adapters + GEKA coupling
- Releasing tool
- Maintenance kit
- 13x19 21 LM air hose with GEKA coupling
- one 10 LM Strike hose
- Compressor unit for Sprinter with mounting
- 17 LM finishing spray lance cord

MIXER[®]

ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

MIXER SPRINTER

MORTAR - 2,2 KW

Continuous mixing pump | reference : 910000200A



Compact continuous mixing pump, with reduced weight and size, easy to disassemble into 4 sections for simplified transport.

Ideal for a wide range of powder products, lime-, plaster- and cement-based surface coatings. This pump is also ideal for filling joints, resurfacing works, applying adhesives, interior and exterior finishes.

TECHNICAL DATA

Hopper capacity	70 L
Power supply	230 V~ 50 Hz
Motor thermal protection	yes
Variable speed	yes
Water pressure booster	yes
Flow meter	Digital display
Water shortage safety device	yes
Integrated compressor (cat. C5)	8021022700
Spraying flow rate	8 to 26 L/min*
Max. spraying distance	40 meters*
Loading height	102 cm
Dimensions (l x w x h)	98 x 72 x 153 cm
Weight	145 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 20 LM neoprene 3x6 power cord with plug
- Adapters + GEKA coupling
- Releasing tool
- 25x37 15 LM spray hose with couplings
- 13x19 16 LM air hose with GEKA coupling
- Mixer full spray lance made from aluminium tubing
- Compressor unit for Sprinter with mounting
- Maintenance kit

MIXER[®]

ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

MIXER SPRINTER

MORTAR - 3 KW

Continuous mixing pump | reference : 910000212A



Compact continuous mixing pump, with reduced weight and size, easy to disassemble into 4 sections for simplified transport.

Ideal for a wide range of powder products, lime-, plaster- and cement-based surface coatings. This pump is also ideal for filling joints, resurfacing works, applying adhesives, interior and exterior finishes.

TECHNICAL DATA

Hopper capacity	70 L
Power supply	230 V~ 50 Hz
Motor thermal protection	yes
Variable speed	yes
Water pressure booster	yes
Flow meter	Digital display
Water shortage safety device	yes
Integrated compressor (cat. C5)	8021022700
Spraying flow rate	8 to 26 L/min*
Max. spraying distance	40 meters*
Loading height	102 cm
Dimensions (l x w x h)	98 x 72 x 153 cm
Weight	145 kg

(* depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 20 LM neoprene 3x6 power cord with plug
- Adapters + GEKA coupling
- Releasing tool
- 25x37 15 LM spray hose with couplings
- 13x19 16 LM air hose with GEKA coupling
- Mixer full spray lance made from aluminium tubing
- Compressor unit for Sprinter with mounting
- Maintenance kit

MIXER®

 **ETOP**
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

MIXER SPRINTER

FLOOR SCREED

Continuous mixing pump | reference : 910000400A



Compact continuous mixing pump, with reduced weight and size, easy to disassemble into 4 sections for simplified transport.

Ideal for a wide range of powder products, lime-, plaster- and cement-based surface coatings. This pump is also ideal for filling joints, resurfacing works, applying adhesives, interior and exterior finishes.

TECHNICAL DATA

Hopper capacity	70 L
Power supply	230 V~ 50 Hz
Motor thermal protection	yes
Variable speed	yes
Water pressure booster	si
Flow meter	Digital display
Water shortage safety device	si
Integrated compressor (cat. C5)	no
Spraying flow rate	8 to 26 L/min*
Max. spraying distance	40 meters*
Loading height	102 cm
Dimensions (l x w x h)	98 x 72 x 153 cm
Weight	145 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 20 LM neoprene 3x4 power cord
- Adapters + GEKA coupling
- Releasing tool
- 21 LM remote control
- 25x37 10 LM spray hose with couplings

MIXER®

 **ETOP**
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md