

MIXER PLUS SMALL MONO PLASTER - 2.2 KW

Continuous mixing pump | reference : 903105200A



Single-phase (230 V) continuous mixing pump, ideal for spraying pre-mixed surface coatings containing lime, cement, finishing compounds, fillers, coloured compounds, adhesives, screeds, etc. and any product compatible with mechanical spraying.

TECHNICAL DATA

| | |
|------------------------------|-------------------|
| Hopper capacity | 150 L |
| Power supply | 230 V~ 50 Hz |
| Motor thermal protection | yes |
| Variable speed | 3 speeds |
| Water pressure booster | yes |
| Flow meter | yes |
| Water shortage safety device | yes |
| Integrated compressor | 8021008000 |
| Spraying flow rate | 8 to 26 L/min* |
| Max. spraying distance | 40 meters* |
| Loading height | 91 cm |
| Dimensions (l x w x h) | 111 x 72 x 155 cm |
| Weight | 212 kg |

| | |
|-----------------------------------|------------------|
| Gear motor for mixing chamber | 2.2 kW - 320 rpm |
| Gear motor for powder scoop wheel | 0.25 kW - 10 rpm |

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Sprinter cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 20 LM neoprene 3x6 power cord
- Adapter + GEKA coupling
- Releasing tool
- Cleaning part
- 25x37 15 LM spray hose with couplings
- 13x19 16 LM air hose with GEKA coupling
- Mixer full spray lance made from aluminium tubing
- Maintenance kit

MIXER®

 **ETOP**
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

MIXER PLUS SMALL MONO PLASTER - 3 KW

Continuous mixing pump | reference : 903105230A



Single-phase (230 V) continuous mixing pump, ideal for spraying pre-mixed surface coatings containing lime, cement, finishing compounds, fillers, coloured compounds, adhesives, screeds, etc. and any product compatible with mechanical spraying.

TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Hopper capacity | 150 L |
| Power supply | 230 V~ 50 Hz |
| Motor thermal protection | yes |
| Variable speed | 3 speeds |
| Water pressure booster | yes |
| Flow meter | yes |
| Water shortage safety device | yes |
| Integrated compressor | 8021008000 |
| Spraying flow rate | 8 to 26 L/min* |
| Max. spraying distance | 40 meters* |
| Loading height | 91 cm |
| Dimensions (l x w x h) | 111 x 72 x 155 cm |
| Weight | 212 kg |
| Gear motor for mixing chamber | 3 kW - 320 rpm |
| Gear motor for powder scoop wheel | 0.25 kW - 10 rpm |

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Sprinter cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 20 LM neoprene 3x6 power cord
- Adapter + GEKA coupling
- Releasing tool
- Cleaning part
- 25x37 15 LM spray hose with couplings
- 13x19 16 LM air hose with GEKA coupling
- Mixer full spray lance made from aluminium tubing
- Maintenance kit

MIXER[®]

 **ETOP**
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md