

MIXER PLUS CD25

Continuous mixing pump | reference : 903105300A



Single-phase and three-phase continuous mixing pump, ideal for spraying pre-mixed surface coatings containing lime, cement, finishing compounds, fillers, coloured compounds, adhesives, screeds, etc. and any product compatible with the mechanical spraying.

It is fitted with a revolutionary self-diagnostics system that reports any potential malfunctions.

The CD25 operates with a single-phase or three-phase power supply.

TECHNICAL DATA

Tank capacity	150 L
Power supply	230 V or 400 V - 50 Hz
Motor thermal protection	yes
Gear motor for mixing chamber	3 kW - 320 rpm
Gear motor for powder scoop wheel	0.25 kW - 10 rpm
Variable speed	3 speeds
Compressor	8021008000
Water pressure booster	yes
Flow meter	yes
Water shortage safety device	yes
Spraying flow rate	8 to 32 L/min*
Max. spraying distance	40 metres*
Loading height	91 cm
Dimensions (l x w x h)	110 x 72 x 155 cm
Weight	240 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Sprinter cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 50 LM neoprene 4x2.5 power cord
- Adapter + GEKA coupling
- Releasing tool
- Cleaning part
- 25x37 15 LM spray hose with couplings
- 13x19 16 LM air hose with GEKA coupling
- Mixer full spray lance made from aluminium tubing
- Tool bag
- 20 LM neoprene 3x6 power cord with plug
- 50 LM neoprene 5x2,5 power cord with plug

MIXER[®]

ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md