

# MIXER PLUS CLASSIC

Continuous mixing pump | reference : 903100800S



Mixer Plus Top, Mixer Plus Standard and Mixer Plus Classic are three-phase (400 V) continuous mixing pumps, ideal for spraying pre-mixed surface coatings containing lime, cement, finishing compounds, fillers, coloured compounds, adhesives, screeds, etc. and any product compatible with the mechanical spraying.

The Classic model is equipped with an electromechanical control panel containing no electronic components.

## TECHNICAL DATA

Hopper capacity	150 L
Power supply	400 V - 50 Hz
Motor thermal protection	yes
Variable speed	no
Water pressure booster	yes
Flow meter	yes
Water shortage safety device	yes
Integrated compressor	3B02600000
Spraying flow rate	6 to 50 L/min*
Max. spraying distance	40 meters*
Loading height	91 cm
Dimensions (l x w x h)	111 x 72 x 155 cm
Weight	249 kg
Gear motor for mixing chamber	5.5 kW - 400 rpm - 50 Hz
Gear motor for powder scoop wheel	0.5 kW - 28 rpm

(\* ) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

## DELIVERED WITH

- Anti-seize spray
- Sprinter cleaning shaft
- 19x26 20 LM water hose with GEKA coupling
- 25 LM neoprene 4x2.5 power cord with plug
- Adapter + GEKA coupling
- Releasing tool
- Cleaning part
- 25x37 15 LM spray hose with couplings
- 13x19 16 LM air hose with GEKA coupling
- Mixer full spray lance made from aluminium tubing
- Maintenance kit
- PVC Compressor Protection

**MIXER**<sup>®</sup>

**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chişinău, str. Uzinelor 90  
+ /373/ 67 707 707  
office@etop.md  
www.etop.md