

MIXER PLUS TOP

Continuous mixing pump | reference : 903100900A



Mixer Plus Top and Mixer Plus Standard are three-phase (400 V) continuous mixing pumps, ideal for spraying pre-mixed surface coatings containing lime, cement, finishing compounds, fillers, coloured compounds, adhesives, screeds, etc. and any product compatible with the mechanical spraying.

The Plus Top model is fitted with a revolutionary self-diagnostic system that report any potential malfunctions.

TECHNICAL DATA

Hopper capacity	150 L
Power supply	400 V
Motor thermal protection	yes
Variable speed	no
Water pressure booster	yes
Flow meter	yes
Water shortage safety device	yes
Integrated compressor	9002005000
Spraying flow rate	6 to 50 L/min*
Max. spraying distance	40 meters*
Loading height	91 cm
Dimensions (l x w x h)	111 x 72 x 155 cm
Weight	249 kg

Gear motor for mixing chamber	5.5 kW - 400 rpm - 50 Hz
Gear motor for powder scoop wheel	0.5 kW - 28 rpm

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and lenght of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Sprinter cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 50 LM neoprene 4x2.5 power cord with plug
- Adapter + GEKA coupling
- Releasing tool
- Cleaning part
- 25x37 15 LM spray hose with couplings
- 13x19 16 LM air hose with GEKA coupling
- Mixer full spray lance made from aluminium tubing
- Maintenance kit
- PVC Compressor Protection

MIXER[®]

ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md