

MIXER FLATSPRAY 15

Airless atomizers | reference : 3B03207000



FLATSPRAY 15 enables application of all types of pasty film fillers. It is a compact, quiet and light machine.

It can be moved up and down stairs by only one person, thanks to its trolley-type chassis. Cleaning can be made rapidly, only at the very end of the project and the pump can be changed in 5 minutes directly on the construction site.

The machine is equipped with a ball nose pump with integrated filter. Starting is wireless when the gun is opened.

The quick-release hoses make it easier to use on site.

APPLICATIONS

All types of ready-to-use film plasters: smoothing coating, raking coating, casing coating, bituminous coating...

TECHNICAL DATA

Maximum working pressure	120 bar
Maximum product flow-rate	6/L min*
Electric motor	2,2 kW
Power	230 V / 50 and 60 Hz
Type of pump	volumetric screw pump
Pump	JET 2
Tank capacity	57 L
Max nozzle size	0,045"
Dimensions (l x w x h)	113 x 61 x 78 cm
Weight	62 kg
Noise level	91 Lwa

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- a Ø16 x 15 m hose
- a spray-gun with nozzle holder
- a TT3 435 nozzle
- 1 toolbox containing:
 - two spanners 17 and 22
 - a multigrip pliers
 - three Allen keys Ø2, 5 and 8
 - two cleaning balls and a cleaning brush
 - 1 L of storage liquid

MIXER[®]

ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md