

MIXER FLATSPRAY 20

Airless atomizers | reference : 3B03203000



Mixer Flatspray 20 is fitted with a valveless pump for easy maintenance, a stainless steel round tank and a Ø35 mm drain valve to facilitate cleaning.

Its inflatable wheels with their flat profile improve stability and allow the machine to be easily moved, even when the tank is full.

APPLICATIONS:

All types of ready-to-use film plasters: smoothing coating, raking coating, casing coating, bituminous coating...

Droplet-finish surface coatings* and other products.

*avec compresseur et kit gouttelette en option

TECHNICAL DATA

| | |
|-------------------------|---------------------------|
| Hopper capacity | 110 L |
| Power supply | 230 V-16 A / 50 and 60 Hz |
| Motor power | 2,2 KW |
| Max. operating pressure | 120 bar |
| Max. spraying flow rate | 6L/min* |
| Max. spraying distance | 40 meters* |
| Type of pump | volumetric screw pump |
| Pump | JET 2 |
| Max. nozzle (new) | 0.045'' |
| Dimensions (l x w x h) | 143 x 65 x 97 cm |
| Weight | 90 kg |

(* depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- a Ø16 x 20 m hose
- a Jetpro spray-gun with nozzle holder
- a TT3 443 nozzle
- a toolbox containing:
 - a 17 spanner
 - two open-end wrenches 22/32 and 27/38
 - a multigrip plier
 - three Allen keys Ø2, 5 and 8
 - two cleaning balls and a cleaning brush
 - 1 L of storage liquid

MIXER[®]

ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md