

MIXER FLATSPRAY 30

Airless atomizers | reference : 3B03204000



Mixer Flatspray 30 is fitted with a valveless pump for easy maintenance, a stainless steel round tank and a Ø35 mm drain valve to facilitate cleaning.

Its large inflatable wheels allow the machine to be easily moved, even when the tank is full.

APPLICATIONS :

All types of ready-to-use film plasters: smoothing coating, raking coating, casing coating, bituminous coating ...

Droplet-finish surface coatings* and other products.

*with optional droplet-finish kit and compressor

TECHNICAL DATA

Hopper capacity	110 L
Power supply	230 V-16 A / 50 and 60 Hz
Motor power	3 kW
Max. operating pressure	120 bar
Max. spraying flow rate	7L/min*
Max. spraying distance	60 meters*
Type of pump	volumetric screw pump
Pump	JET 2
Max. nozzle (new)	0.055"
Dimensions (l x w x h)	143 x 65 x 97 cm
Weight	100 kg

(* depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- a Ø19 x 30 m hose
- a Ø16 x 2,5 m easy handling flexible hose
- a wireless remote control
- a Jetpro spray-gun with nozzle holder
- a TT3 443 nozzle
- a toolbox containing:
 - a 17 spanner
 - a multigrip plier
 - three Allen keys Ø2, 5 and 8
 - two cleaning balls and a cleaning brush
 - 1 L of storage liquid

MIXER[®]

ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md