

MIXER FLATSPRAY 40

Airless atomizers | reference : 3B03204100



Mixer Flatspray 40 is a machine for applying thin films of filler.

It uses a valveless pump, is easy to maintain, with a round stainless steel tank for easy cleaning, a Ø35 mm drain valve. It is equipped with large diameter, flat profile, inflatable tyres for better stability.

The machine is equipped with a ball nose pump with integrated filter. Starting is wireless when the gun is opened.

The quick-release hoses make it easier to use on site..

APPLICATIONS :

All types of ready-to-use film plasters: smoothing coating, raking coating, casing coating, bituminous coating ...

Can also make droplet type applications with an optional kit and a compressor

TECHNICAL DATA

Hopper capacity	110 L
Power supply	400 V Tri / 50 & 60 Hz
Motor power	3,3 kW
Max. operating pressure	130 bar
Max. spraying flow rate	9 L/min*
Max. spraying distance	60 meters*
Type of pump	volumetric screw pump
Pump	JET 5
Max. nozzle (new)	0.065''
Dimensions (l x w x h)	143 x 65 x 97 cm
Weight	110 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- a Ø19 x 30 m hose
- a Ø16 x 2,5 m easy handling flexible hose
- a wireless remote control
- a Jetpro spray-gun with nozzle holder
- a TT3 443 nozzle
- a toolbox containing:
 - two spanners 17 and 22
 - a multigrip plier
 - three Allen keys Ø2, 5 and 8
 - two cleaning balls and a cleaning brush
 - 1 L of storage liquid

MIXER[®]

ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md