



**WACKER  
NEUSON**  
*all it takes!*



## IE 58/42/5

### High-frequency internal vibrators

Simple and effective

The internal vibrators of Wacker Neuson's IE series are equipped with a high frequency electric motor, thus achieving good results in concrete consolidation. At the same time, the user benefits from the ergonomically built housing that makes handling pleasant.

## Highlights

- High-performance electric motor with stable speeds
- Made in Germany
- Sturdy design

## Technical Data

### ■ Electrical - Output Details

Nominal current	12.00 A
Nominal voltage	42.0 V
Nominal frequency	200.0 Hz
Nominal power [P]	0.70 KW
Phase	3.0 ~

### ■ Mechanical - Output Details

Amplitude at air	2.900 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz

### ■ Mechanical Details

Length Hose	5.0 m
-------------	-------

Weight	14.30 kg
Rubber cap	no

### ■ Motor

Motor type	Asynchronous motor
------------	--------------------

### ■ Environment Data

Protection class	III / Safety extra-low voltage
Degree of protection	IP67

### ■ Electrical System

Breaker Switch On/Off	Yes
Integrated transformer	No
Length Cable	15.0 m
Kind of plug	CEE-Plug 3P 32A 42V 4H



**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chișinău, str. Uzinelor 90  
+ /373/ 67 707 707  
office@etop.md  
www.etop.md