



**WACKER
NEUSON**
all it takes!



FUE10/042/200

Stationary frequency converters

Safety and output for long-term application

When it comes to safety and high output during long-term application there is no compromise with these electronic frequency converters. Besides, they are very sturdy and maintenance-free. Their high-quality components and the all-round housing offer protection against shocks, impacts and water.

Highlights

- Completely maintenance-free
- Secure protection

Technical Data

■ Electrical - Output Details

Nominal current	24.50 A
Nominal voltage	400.0 - 415.0 V
Nominal frequency	50.0 - 60.0 Hz
Output current	145.0 A
Output voltage	42.0 V
Output frequency	0.0 - 200.0 Hz
Phase	3.0 ~
Output Phase	3.0 ~

■ Mechanical Details

Length	500.0 mm
Width	500.0 mm

Height	550.0 mm
Weight	87.00 kg

■ Environment Data

Protection class	I / Protective earthing
Degree of protection	IP54

■ Electrical System

Breaker Switch On/Off	Yes
Operating indicator	yes
Adjusting frequency	yes
Length Cable	2.5 m
Kind of plug	CEE-Plug 5P 32A 400V 6H



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md