

2-SPEED IMPACT DRILL

SB 13/2 RLE



SB 13/2 RLE applications

- Drilling in masonry and concrete
- Drilling anchor holes
- Small and large drill holes (1st/2nd gear)
- Installing screws, also large screws
- Mixing and stirring viscous substances
- Working with hole saws
- Sinking sockets with core bits
- Removing paint and rust with a brush
- Polishing

SB 13/2 RLE features

- Rapid changeover, drilling/percussion drilling
- High torque in 1st gear (45 Nm)
- High speed in 2nd gear
- Speed and impact force infinitely adjustable with pushbutton switch/adjusting dial
- Clockwise/anticlockwise selector switch
- High-strength magnesium gear housing
- Robust heavy-duty drill spindle mounting
- 3-level reduced 2-speed gear
- High quality keyless chuck for a rapid and easy tool change

TECHNICAL DATA

SB 13/2 RLE

Rated power	650 W	
Screws up to	dia. 12 mm	
Set torque (1st gear)	45 Nm	
Machine weight	2.0 kg	
Drill spindle thread	1/2" - 20 UNF	
Spindle collar dia.	43 mm	
Max. impact rate	42000 impacts/min	
Chuck clamping range	dia. 1.5 - 13 mm	
Drilling dia. in	1st gear	2nd gear
steel	16 mm	8 mm
softwood	40 mm	20 mm
stone	20 mm	13 mm
lightweight materials with hole saw	105 mm	50 mm
sand-lime brick and masonry with core bit	66 mm	-
Rated speed	0 - 450 rpm	0 - 1550 rpm

Order-No. SB 13/2 RLE

Standard specification: DUSS SB 13/2 RLE 2-speed impact drill, keyless chuck with locking screw, side handle, depth stop.