

## ROTARY HAMMER

### P 26 SDS



#### P 26 SDS applications

- Drilling anchor holes, also overhead
- Drilling through-holes up to dia. 30 mm for heating pipes, electrical cables, etc.
- Sinking sockets in masonry up to dia. 82 mm
- Facade construction, metal and wooden structures
- Installing electrical, plumbing and heating systems

#### P 26 SDS features

- Safety clutch with gentle starting torque (protects against injuries, overloading and tool breakages)
- Speed and impact force infinitely adjustable with pushbutton switch for gentle drilling with pinpoint accuracy
- Trigger lock, ensuring non-fatiguing continuous operation, such as drilling rows of holes
- Vibration damped percussion mechanism
- Vibration damping elements
- Hammer action off-switch for drilling into wood, steel, tiles, etc.
- Rapid tool change
- Robust construction (outside: fibreglass reinforced polyamide; inside: magnesium housing)



#### TECHNICAL DATA

#### P 26 SDS

|                                    |                      |
|------------------------------------|----------------------|
| Rated power                        | 710 W                |
| Drilling range with drill bit      | dia. 5 - 30 mm       |
| Drilling range with core bit       | dia. 40 - 82 mm      |
| Drilling range in steel            | up to dia. 13 mm     |
| Drilling performance* (dia. 20 mm) | 240 mm/min           |
| Single impact energy               | 0 - 3.6 J            |
| Rated speed                        | 0 - 700 rpm          |
| Impact rate, adjustable            | 0 - 3700 impacts/min |
| Machine weight                     | 3.6 kg               |
| Chuck                              | SDS-plus             |

\* In hard C45/55 concrete

#### Order-No. P 26 SDS

Standard specification: DUSS P 26 SDS rotary hammer, side handle, tube of grease, dust cup, depth stop, carrying case for machine and tools.