



P 26 C applications

- Drilling anchor holes
- Drilling through-holes up to dia. 30 mm for heating pipes, electrical cables, etc.
- Sinking sockets in masonry up to dia. 82 mm
- Light chiselling work
- Repair work, also overhead
- Precision chiselling work
- Facade construction, metal and wooden structures
- Installing electrical, plumbing and heating systems

P 26 C features

- Speed and impact force infinitely adjustable with pushbutton switch for gentle drilling with pinpoint accuracy
- Rapid changeover from hammer drilling to chiselling and vice versa
- Chisel can be positioned in twenty ways
- Vibration damping elements
- Maintenance-free (with lifetime lubrication)
- Rapid tool change
- Low-wear safety clutch

TECHNICAL DATA	P 26 C
Rated power	710 W
Drilling range with drill bit	dia. 5 - 30 mm
Drilling range with core bit	dia. 40 - 82 mm
Drilling performance* (dia. 14 mm)	460 mm/min
Drilling performance* (dia. 20 mm)	240 mm/min
Chiselling performance* with pointed chisel	approx. 50 kg/h
Single impact energy	0 - 3.6 J
Rated speed	0 - 700 rpm
Impact rate, adjustable	0 - 3700 impacts/min
Machine weight	3.9 kg
Chuck	SDS-plus

* In hard C45/55 concrete

Order-No. P 26 C

Standard specification: DUSS P 26 C combi hammer, side handle, tube of grease, dust cup, depth stop, carrying case for machine and tools.