

P 60 A



P 60 A applications

- Drilling medium-sized holes
- Sinking sockets
- Medium-category chiselling work
- Chasing grooves and slots
- Repair work

P 60 A features

- Active vibration damping (RVA), ensuring comfortable continuous use
- Screw-in, vibration damped auxiliary handle for non-fatiguing, back-saving posture when drilling and chiselling downwards
- LED display for optimum service planning
- Consistently high engine output thanks to optimised engine cooling
- Electronic for constant speed control
- Speed and impact force infinitely adjustable with adjusting dial
- Rapid changeover from hammer drilling to chiselling and vice versa
- Chisel can be positioned in twenty ways
- Maintenance-free (with lifetime lubrication)
- Low-wear safety clutch



| TECHNICAL DATA | P 60 A |
|---|--------------------------|
| Rated power | 1000 W |
| Drilling range with drill bit | dia. 8 - 55 mm |
| Drilling range with core bit | dia. 55 - 100 mm |
| Drilling performance* (dia. 30 mm) | 130 mm/min |
| Chiselling performance* with pointed chisel | approx. 105 kg/h |
| Single impact energy | 3.3 - 8.5 Joule |
| Rated speed | 130 - 250 U/min |
| Impact rate, adjustable | 1670 - 3200 impacts/min |
| Machine weight | 7.2 kg |
| Chuck | 19 mm hexagon |
| Vibration data | drilling/chiselling |
| Normal setting | 8.9/7.3 m/s ² |
| Compressor setting | 8.2/6.8 m/s ² |

* In hard C45/55 concrete



Order-No. P 60 A

Standard specification: Duss P 60 A combi hammer, side handle, auxiliary handle, tube of grease, carrying case for machine and tools.