

### PX 48 A



#### PX 48 A applications

- Drilling anchor holes, fastening cladding panels
- Overhead work and drilling rows of holes
- Sinking sockets
- Removing plaster and tiles
- Cleaning up surfaces
- Chasing grooves and slots
- Precision repair work

#### PX 48 A features

- Outstanding drilling and chiselling performance
- Active vibration damping (RVA), ensuring comfortable continuous use
- Exceptionally light weight and low vibration
- Electronic for constant speed control
- Speed and impact force infinitely adjustable with pushbutton switch/adjusting dial
- Rapid changeover from hammer drilling to chiselling and vice versa
- Chisel can be positioned in twenty ways
- Maintenance-free (with lifetime lubrication)
- Low-wear safety clutch



TECHNICAL DATA	PX 48 A
Rated power	920 W
Drilling range with drill bit	dia. 8 - 55 mm
Drilling range with core bit	dia. 45 - 90 mm
Drilling performance* (dia. 25 mm)	270 mm/min
Chiselling performance* with pointed chisel	approx. 125 kg/h
Single impact energy	0 - 7 J
Rated speed	0 - 480 rpm
Impact rate, adjustable	0 - 3700 impacts/min
Machine weight	5.5 kg
Chuck	SDS-max
Vibration data	drilling/chiselling
Normal setting	6.8/5.5 m/s <sup>2</sup>

\* In hard C45/55 concrete

#### Order-No. PX 48 A

Standard specification: DUSS PX 48 A combi hammer, side handle, tube of grease, carrying case for machine and tools.