

### PX 78



#### PX 78 applications

- Drilling medium-sized holes
- Drilling through-holes
- Sinking sockets
- Medium-category chiselling work
- Chasing grooves and slots
- Repair work

#### PX 78 features

- Outstanding drilling and chiselling performance
- Active vibration damping (RVA), ensuring comfortable continuous use
- Screw-in, vibration damped auxiliary handle for non-fatiguing, back-saving posture when drilling and chiselling downwards
- LED display for optimum service planning
- Consistently high engine output thanks to optimised engine cooling
- Electronic for constant speed control
- Speed and impact force infinitely adjustable with adjusting dial
- Rapid changeover from hammer drilling to chiselling and vice versa
- Chisel can be positioned in twenty ways
- Maintenance-free (with lifetime lubrication)
- Low-wear safety clutch



TECHNICAL DATA	PX 78
Rated power	1500 W
Drilling range with drill bit	dia. 12 - 80 mm
Drilling range with core bit	dia. 45 - 150 mm
Drilling performance* (dia. 35 mm)	160 mm/min
Chiselling performance* with pointed chisel	approx. 200 kg/h
Single impact energy	4.5 - 10 J
Rated speed	170 - 310 rpm
Impact rate, adjustable	1800 - 3370 impacts/min
Machine weight	7.6 kg
Chuck	SDS-max
Vibration data	drilling/chiselling
Normal setting	9.8/6.8 m/s <sup>2</sup>
Compressor setting	8.2/6.3 m/s <sup>2</sup>

\* In hard C45/55 concrete

#### Order-No. PX 78

Standard specification: Duss PX 78 combi hammer, side handle, auxiliary handle, tube of grease, carrying case for machine and tools.