

## BREAKERS

### PK 45 · PK 45 A



#### PK 45 · PK 45 A applications

- Removing plaster and tiles
- Chasing grooves and slots
- Chiselling work
- Cleaning up surfaces
- Producing breaches and openings
- Precision repair work

#### PK 45 · PK 45 A features

- Pneumatic impact mechanism designed for optimum efficiency
- Trigger lock, ensuring non-fatiguing work
- Electronic for constant impact rate control
- Impact rate and impact force infinitely adjustable with pushbutton switch/adjusting dial
- Robust, 16 mm hexagon chuck for prolonged service life
- Vibration damping elements
- Maintenance-free (with lifetime lubrication)

#### PK 45 A additional features

- Active vibration damping (RVA), ensuring comfortable continuous use



TECHNICAL DATA	PK 45	PK 45 A
Rated power	710 Watt	710 Watt
Chiselling performance*	approx. 100 kg/h	approx. 100 kg/h
Single impact energy	0 - 6.4 Joule	0 - 6.4 Joule
Impact rate, adjustable	0 - 3000 impacts/min	0 - 3000 impacts/min
Machine weight	4.5 kg	4.9 kg
Chuck	16 mm hexagon	16 mm hexagon
Vibration data PK 45 A		chiselling
Normal setting		6.8 m/s <sup>2</sup>

\* In hard C45/55 concrete with pointed chisel

#### Order-No. PK 45 · PK 45 A

Standard specification: DUSS PK 45 · PK 45 A breaker, side handle, tube of grease, carrying case for machine and tools.