

S6000 (24L) 400V #IPP

THE COMPLETE DIESEL PACKAGE



Showing the excellence of Pramac's professional equipment, this generator offers a robust package with a modern and economical Diesel engine. Perfect for intensive use, it's equipped with a control panel which allows to integrate many accessories and options for better confort and for optimal command.

Main Features

| | | |
|--------------|------------|---------|
| Frequency | Hz | 50 |
| Voltage | V | 400/230 |
| Power factor | cos ϕ | 0.8 |
| Phase | | 3 |

Power Rating

| | | |
|-----------------------------|-----|-----|
| Emergency Standby Power ESP | kVA | 6.9 |
| Emergency Standby Power ESP | kW | 5.5 |
| Continuous power COP | kVA | 5.6 |
| Continuous power COP | kW | 4.5 |

Single Phase Power Rating

| | | |
|-----------------------------------|-----|-----|
| Single phase Maximum Power | kVA | 3.2 |
| Single phase continuous power COP | kVA | 3.0 |

Ratings definition (According to standard ISO8528 1:2005)



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chişinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

Engine specifications

| | | |
|-------------------------|-----------------|----------------|
| Engine Brand | | Yanmar |
| Model | | L100N Electric |
| Engine cooling system | | Air |
| Displacement | cm ³ | 435 |
| Aspiration | | Natural |
| Operating Speed-Nominal | rpm | 3000 |
| Speed governor | | Mechanical |
| Fuel | | Diesel |
| Oil capacity | l | 1.6 |
| Starting system | | Electric |

Alternator Specifications

| | | |
|---------------------------|----|----------|
| Alternator | | NSM |
| Type | | Brushes |
| Class | | H |
| IP protection | | 23 |
| Poles | | 2 |
| Frequency | Hz | 50 |
| Voltage | V | 400 |
| Voltage regulation system | | Compound |
| Voltage tolerance | % | 6 |

Dimensional data

| | | |
|--------------------|--------|-----|
| Length | (L) mm | 840 |
| Width | (W) mm | 641 |
| Height | (H) mm | 696 |
| Dry weight | kg | 124 |
| Fuel tank capacity | l | 24 |

Autonomy

| | | |
|----------------------------------|-----|-------|
| Fuel consumption at 75% of Load | l/h | 1.46 |
| Fuel consumption at 100% of Load | l/h | 1.94 |
| Running time at 75% of load | h | 16.44 |
| Running time at 100% of load | h | 12.37 |



GENSET CONTROL PANEL (IPP)



Mounted on the genset and complete of: instrumentation, control, protection of the generating set and sockets.

COMMANDS

- Start selector switch with key: OFF - ON - START

INSTRUMENTATION (DGT)

- Voltmeter
- Hours-counter
- Frequency-meter

PROTECTIONS

- Circuit breaker
- Isometer protection (IPP)
- Fuse DC 10A
- Low Oil Pressure

OUTPUT

- Battery charged 12V 10A

SOCKET TYPE

| | |
|--------------------------|---|
| SCHUKO 230V 16A IP54 | 1 |
| 2P+T CEE 230V 16A IP44 | 2 |
| 3P+N+T CEE 400V 16A IP44 | 1 |



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md

ACCESSORIES

TRANSPORTATION KIT

- With fix handles



- With folding handles

