

# PMi 6500



Pramac PMi series inverter: optimal solution to combine silent operation with less fuel consumption and tension stability; the inverters Pramac stabilize the output tension and supply power for all kinds of equipment. They guarantee maximum efficiency: adjusting the speed according to the required load, our inverters reduce the average fuel consumption.

## FEATURES

- Inverter technology: stable power for safe operation of sensitive electronics.
- OHV engine provides consistent power for multiple applications.
- Low-oil level shutdown automatically safeguards engine from damage.
- Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction.
- ATS connector
- Remote control
- 2 wire start
- Lightweight and compact.
- Wheel kit integrated for easy transportation
- Fuel gauge allows user to track gasoline levels



## PERFORMANCE

Frequency	Hz	50
Voltage	V	230
Phase		1
Max Power	watt	6500
Rated Power	watt	6000



**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chişinău, str. Uzinelor 90  
+ /373/ 67 707 707  
office@etop.md  
www.etop.md

Engine		
Brand		Pramac
Type		OHV
Exhaust emission level		Stage V
Operating Speed Nominal	rpm	Variable
Fuel		Petrol
Starting Systems		Electric (+Recoil)
Oil capacity	l	0.85
Low Oil Shutdown		✓

Alternator	
Voltage regulation system	Inverter

Dimensional data		
Length	(L) mm	625
Width	(W) mm	448
Height	(H) mm	560
Dry weight	kg	50.5
Carton box dimension LxWxH	mm	680x500x610

Autonomy		
Fuel tank capacity		14
Fuel consumption 50%	l/h	2.1
Running time 50% (Eco Mode)	h	6.6

Noise level		
Guaranteed noise level (LWA)	dB(A)	96
Noise pressure level @ 7 m	dB(A)	68

## GENSET CONTROL

### COMMANDS:

- Electric start button
- Smart throttle: Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction
- ATS connector / 2 wire start / Remote control

### INSTRUMENTATION:

- Voltage (V), Frequency (Hz) , Running time (h)
- Oil alarming / output power / Fuel level indicator on the tank
- 12V battery maintainer holder

### PROTECTIONS

- Overcurrent / Overspeed / High temperature / AC thermal circuit breaker / DC circuit breaker

### OUTPUT:

- DC12V 6A

### SOCKET TYPE

SCHUKO 230V 16A IP44	1
2P+T CEE 230V 32A IP44	1



**3XTRA**  
CONTROL



**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chişinău, str. Uzinelor 90  
+ /373/ 67 707 707  
office@etop.md  
www.etop.md