

SX PLUS 5/25 LFP



Key Features

- Single Phase Output
- User-friendly control and operator interface
- GSM Remote monitoring
- Stackable (up to 2 units)
- Easy handling
- Simple and fast commissioning



Output Specifications

Nominal Output power (continuous)	kVA	5
Peak Output power (5s)	kW	10
Rated voltage (single phase)	V	230
Frequency	Hz	50
Phase (s)		1
Nominal energy capacity	kWh	24.0
Reference ambient temperature	°C	25



System data

System pass-through capacity	A	50
Operating temperature range	°C	-10.. +50
Degree of protection	IP	44
Noise pressure @1m (LpA)	dB(A)	56.7



Inverter

Quantity	n.	1
Rated apparent power	kVA	5
Power factor / Range		±0.8



Battery specifications

Battery modules quantity	n.	5
Battery (Type)		Li-Ion LFP
Module capacity	kWh	4.8
Battery rated Voltage	VDC	48
Depth of Discharge (DoD)	%	90
Battery design life	cycles	6000
Usable energy @ DoD / AC side	kWh	20.5
Total batteries weight	kg	200



Instruments, controls & connections

Inverter protection Short Circuit	✓
Inverter protection Overload	✓
Inverter protection Over Temperature	✓
Inverter protection Low Battery	✓
System status control panel	✓
Battery condition	✓
Battery main isolator	✓
Remote monitoring device	✓
Automatic generator auto-start signal	✓



Input Power Connection

16A CEE 2P+T - GRID	1
32A CEE 2P+T - DG	1




Output Power Connection

16A Schuko	1
16A CEE 2P+T	2
32A CEE 2P+T	1
Individual RCD 1phase sockets	✓




Overall Dimensions

Dimensions	(L/W/H) mm	1077x1105x1130
Weight	kg	502



Optional

1xSolar Charge Controller 5.8kW 250V	MPPT
Cold Weather Kit	CWK



ETOP
creat să reziste

Republica Moldova, MD-2023
mun. Chișinău, str. Uzinelor 90
+ /373/ 67 707 707
office@etop.md
www.etop.md