



**WACKER  
NEUSON**  
*all it takes!*



## LTT6

### Light Tower

#### Powerful and Compact

The LTT4 and LTT6 light towers offer a smaller footprint and the long-lasting LED's deliver exceptional light coverage for a variety of applications where temporary lighting is needed. The units are equipped with auxiliary power which adds to the versatility of these machines.

### Highlights

- LED Lights
- Programmable Controller
- Compact Design
- Standard Auxiliary Power
- Telescopic Vertical Mast

### Technical Data

#### ■ Mechanical Details

Length	2,563.0 mm
Width	1,207.0 mm
Height	2,548.0 mm
Operating weight	705.0 kg
Mast height max.	7.0 m

#### ■ Generator

Output frequency	60.0 Hz
Voltage accuracy	10.0 %
Generator Rating 1~ (Continuous)	6.0 KW
Generator Manufacturer	Mecc Alte

#### ■ Engine

Cooling	Water-cooling
Engine type	Diesel engine

Cylinder	3.0
Cylinder capacity	1,028.0 cm3
Fuel	Winter Blend Diesel No. 2
Tank capacity	198.4 l
Effective power	8.4 KW
Operating Engine speed	1,800.0 1/min
Exhaust-gas limit	EPA Tier 4 final
Engine Manufacturer	Kohler

#### ■ Electrical System

Lighting appliances	320W (LED)
Bulb power	320.0 W

#### ■ Operating Fluids

Fuel consumption (Lights only)	1.1 L/hr
Run Time (Lights only)	173.4 hrs



**ETOP**  
creat să reziste

Republica Moldova, MD-2023  
mun. Chişinău, str. Uzinelor 90  
+ /373/ 67 707 707  
office@etop.md  
www.etop.md